

# Small SWaP Digital SIGINT System (SSDSS)

SNC's SSDSS Receiver Processor Unit (RPU) provides a powerful, multi-channel, multi-operator solution capable of detection, interception, identification and direction finding of complex radar emitters in a small size, weight and power (SWaP) form factor.

### SYSTEM ATTRIBUTES

- · Multi-channel, Multi-operator signal acquisition
- Three wideband tuners and three digital receivers
- · Wideband and narrowband processing, five bandwidths
- · Controls RF switch matrix for antenna selection
- Interfaces to one or two spinning DF antennas
- Analog IF outputs from three tuners feed CDIF recorders
- · Analyze pulsed, CW and low-powered FMCW signals
- · Small form factor, lightweight for flexible installation

### **TECH ELINT SYSTEM**

The SSDSS RPU is the heart of a manual Technical ELINT system and can be configured to meet a wide array of user requirements for frequency coverage, antenna coverage, probability of intercept and system sensitivity. The RPU has three independent Collection Elements (CE). Each CE consists of one microwave tuner and one digital signal processing block. Each CE can be tuned from 0.5 to 18 GHz and each CE can control an RF switch matrix to select inputs from different antennas, block down-converters and block up-converters. The SSDSS controls ELINT system up-converters and down-converters to operate from 20 MHz to 40 GHz. For ELINT systems supporting multiple operators, multiple SSDSS assemblies may be connected to work in parallel.

The SSDSS RPU is at the end of the ELINT system RF processing chain. It receives, digitizes and processes complex pulsed, CW and FMCW signals and generates PDWs with associated IQ samples for signal identification and geolocation.

# **CONTROL, DISPLAY & ANALYSIS**

ELINT operators control antenna input selection to each of their assigned CE's, control the spinning DF antennas, tune CE frequencies from 20 MHz to 40 GHz, set RF and IF gain control, control the processing bandwidths, set the threshold type and level, and control signal isolation tools.

ELINT operators interact with real-time situational awareness displays to detect signal activity, isolate signals in dense RF environments and optimize the system settings for the best signal collection. The SSDSS RPU provides interpulse and intrapulse measurement displays to support signal analysis and identification of complex emitters. Real-time user displays include:

- RF Panoramic Display showing signal activity
- Amplitude vs. Frequency Display with qualification tools
- · Waterfall Display showing signal frequency vs. time
- Interpulse and intrapulse analyses
- · Polar and Linear DF Display

## SSDSS RPU CHARACTERISTICS

Input frequency	250 MHz to 18.25 GHz
IF bandwidths	500, 80, 25, 10 and 5 MHz
Form factor	½ Air Transport Rack (ATR) chassis
Size	6.25" W x 10.03" H x 19.3" D
Weight	48 pounds
Power	+28VDC per MIL-STD-704F, 700W
Cooling	Forced air cooling via internal fan
External inputs	10 MHz, 1 PPS, Blanking
IF outputs	3 Wideband and 3 Narrowband
Control and Data Inte	<b>erface</b> Gigabit Ethernet





